

# Pneumatic Crimping Applicator


## RSA-JNA-20S



**7 DAYs**  
lead time


### Feature

- Adjustment : C.H. / I.H. Adjustment Accuracy 0.02mm, Adjustment Range 2.0mm, which show strong adjustment feeling and make sure easier operation.



0.02mm/step

The crimp height  $\pm 0.2\text{mm}$  for each step of the adjusting screw.



The crimp height  $\pm 0.2\text{mm}$  for each movement of the pointer.

- Modularized framework: user-friendly and reduce the maintenance cost;
- Pneumatic feeding mechanism: 40mm terminal pitch and feeding speed is adjustable. Compact cylinder and guide cylinder to choose from, both can enable you to operate the machine freely;
- Reversing value structure: Bulid-in reversing value is stable and reliable;
- Quick change: Perfectly fit with ShinMaywa, JAM and KODERA semi-auto crimping machine;
- Technical documents: You can get a complete technical document containing all the information needed to safely use and correctly maintain the equipment. Upon request, a capability study & Cross-section Analysis could be provided;
- Strong resistance to rust: QW surface plating;
- Production tracking: Laser labeling for each part-unique ID.
- Surface treatment is optional.

### Specification

| Model              | RSA-JNA-20S                       |
|--------------------|-----------------------------------|
| Stroke             | 30mm                              |
| Feeding type       | Side Feed                         |
| Shut Height        | 119.7mm(4.713in)                  |
| Wire Size          | 0.08 ~ 6mm <sup>2</sup> (9~28AWG) |
| Terminal Thickness | 1.2mm (max)                       |
| Feeding System     | Pneumatic                         |
| Terminal Pitch     | 40mm (max)                        |
| weight             | 5KG                               |
| Dimension          | L225mm×W128mm×H100mm              |