

Wire Striping, Twisting Tinning, Crimping Machine

RSE-PTC-10N



Feature

- ▶ One machine multi-function, by change different crimp dies.
- ▶ Foot switch regular or pressure(optional).
- ▶ Pressure Regulator, Adjustable pressure holding time, to ensure accurate crimp adhesion, avoid to the problem of crimping not enough.
- ▶ To use air pressure operation, portable, simple, fast and convenient to carry, crimp time 1000 times/hour, the machine can achieve efficient crimping.

Specification

Model	RSE-PTC-10N
Range of Application	Non-Insulated Terminal $\leq 16\text{mm}^2$; Insulated Terminal $\leq 6\text{mm}^2$; Ferrules Terminal $\leq 35\text{mm}^2$;
Output force	13.5KN
Applicable air pressure	0.4-1 Mpa
Weight	4kg
External dimension	280mm $\times$ 187mm $\times$ 140mm

Sample

Ferrules, 25, 35, 50mm ²	
Twin ferrules, 2 $\times$ 0.5, 1.0, 1.5, 2.0, 2.5, 4, 6, 10mm ²	
Insulated O type or Y type terminals, 1.0, 2.0, 2.5, 4.0, 6.0mm ²	
Non-insulated O type or Y type terminals, 0.5, 1.0, 1.5, 2.0, 2.5, 4.0, 6.0, 10.0mm ²	
Males or females receptacles, 1.0, 2.0, 2.5, 4.0, 6.0mm ²	
Contact pin for rectangular connector, 1.0, 2.0, 4.0mm ²	