

Working temperature >380 °C, high-temperature soldering tip should be customized. (Minimum Order: 50pcs)

Type	Part Number	Specification (W=width;T=thickness)	Remark
911G USB	Thickness: 2.0mm		
	911G-USB5.0x2.0	W5.0mm*T2.0mm (top tining, no slot)	
	911G-USB6.0x2.0	W6.0mm*T2.0mm (top tining, no slot)	
	911G-USB7.0x2.0	W7.0mm*T2.0mm (top tining, no slot)	
	911G-USB8.0x2.0	W8.0mm*T2.0mm (top tining, no slot)	
	911G-USB10x2.0	W10.0mm*T2.0mm (top tining, no slot)	
	911G-USB11x2.0	W11.0mm*T2.0mm (top tining, no slot)	
	911G-USB12x2.0	W12.0mm*T2.0mm (top tining, no slot)	
	911G-USB13x2.0	W13.0mm*T2.0mm (top tining, no slot)	
	911G-USB14x2.0	W14.0mm*T2.0mm (top tining, no slot)	
	911G-USB15x2.0	W15.0mm*T2.0mm (top tining, no slot)	
	911G-USB16x2.0	W16.0mm*T2.0mm (top tining, no slot)	
	911G-USB17x2.0	W17.0mm*T2.0mm (top tining, no slot)	
	911G-USB18x2.0	W18.0mm*T2.0mm (top tining, no slot)	

	911G-USB19x2.0	W19.0mm*T2.0mm (top tining, no slot)	
	911G-USB20x2.0	W20.0mm*T2.0mm (top tining, no slot)	
	911G-USB21x2.0	W21.0mm*T2.0mm (top tining, no slot)	
	Thickness: 2.5mm		
	911G-USB5.0x2.5	W5.0mm*T2.5mm (top tining, no slot)	
	911G-USB6.0x2.5	W6.0mm*T2.5mm (top tining, no slot)	
	911G-USB7.0x2.5	W7.0mm*T2.5mm (top tining, no slot)	
	911G-USB8.0x2.5	W8.0mm*T2.5mm (top tining, no slot)	
	911G-USB9.0x2.5	W9.0mm*T2.5mm (top tining, no slot)	
	911G-USB10x2.5	W10.0mm*T2.5mm (top tining, no slot)	
	911G-USB11x2.5	W11.0mm*T2.5mm (top tining, no slot)	
	911G-USB12x2.5	W12.0mm*T2.5mm (top tining, no slot)	
	911G-USB13x2.5	W13.0mm*T2.5mm (top tining, no slot)	
	911G-USB14x2.5	W14.0mm*T2.5mm (top tining, no slot)	
	911G-USB15x2.5	W15.0mm*T2.5mm (top tining, no slot)	
	911G-USB16x2.5	W16.0mm*T2.5mm (top tining, no slot)	

	911G-USB17x2.5	W17.0mm*T2.5mm (top tining, no slot)	
	911G-USB18x2.5	W18.0mm*T2.5mm (top tining, no slot)	
	911G-USB19x2.5	W19.0mm*T2.5mm (top tining, no slot)	
	911G-USB20x2.5	W20.0mm*T2.5mm (top tining, no slot)	
	911G-USB21x2.5	W21.0mm*T2.5mm (top tining, no slot)	
911G Basic	911G-D (flat head)		
	911G-10D	W1.0mm (one-side tinning, no slot)	
	911G-13D	W1.3mm (one-side tinning, no slot)	
	911G-16D	W1.6mm (one-side tinning, no slot)	
	911G-20D	W2.0mm (one-side tinning, no slot)	
	911G-24D	W2.4mm (one-side tinning, no slot)	
	911G-30D	W3.0mm (one-side tinning, no slot)	
	911G-40D	W4.0mm (one-side tinning, no slot)	
	911G-50D	W5.0mm (one-side tinning, no slot)	
	911G-60D	W6.0mm (one-side tinning, no slot)	
	911G-70D	W7.0mm (one-side tinning, no slot)	

	911G-80D	W8.0mm (one-side tinning, no slot)	
	911G-90D	W9.0mm (one-side tinning, no slot)	
	911G-100D	W10.0mm (one-side tinning, no slot)	
	911G-110D	W11.0mm (one-side tinning, no slot) (Minimum order quantity:50pcs)	
911G Basic	911G-DV1 (flat head)		
	911G-10DV1	W1.0mm (one-side tinning, one-side slot)	
	911G-13DV1	W1.3mm (one-side tinning, one-side slot)	
	911G-16DV1	W1.6mm (one-side tinning, one-side slot)	
	911G-20DV1	W2.0mm (one-side tinning, one-side slot)	
	911G-24DV1	W2.4mm (one-side tinning, one-side slot)	
	911G-30DV1	W3.0mm (one-side tinning, one-side slot)	
	911G-40DV1	W4.0mm (one-side tinning, one-side slot)	
	911G-50DV1	W5.0mm (one-side tinning, one-side slot)	
	911G-60DV1	W6.0mm (one-side tinning, one-side slot)	
	911G-80DV1	W8.0mm (one-side tinning, one-side slot)	

911G Basic		911G-DV2 (flat head)	
	911G-10DV2	W1.0mm (both-sides tinning, top slot) (Minimum order quantity:50pcs)	
	911G-13DV2	W1.3mm (both-sides tinning, top slot)	
	911G-16DV2	W1.6mm (both-sides tinning, top slot)	
	911G-20DV2	W2.0mm (both-sides tinning, top slot)	
	911G-24DV2	W2.4mm (both-sides tinning, top slot)	
	911G-30DV2	W3.0mm (both-sides tinning, top slot)	
	911G-40DV2	W4.0mm (both-sides tinning, top slot)	
	911G-50DV2	W5.0mm (both-sides tinning, top slot)	
	911G-60DV2	W6.0mm (both-sides tinning, top slot)	
911G Basic		911G-PC (shape C)	
	911G-10PC	W1.0mm (Minimum order quantity:50pcs)	
	911G-13PC	W1.3mm	
	911G-16PC	W1.6mm	
	911G-20PC	W2.0mm	
	911G-24PC	W2.4mm	

	911G-30PC	W3.0mm	
	911G-40PC	W4.0mm	
	911G-50PC	W5.0mm	
	911G-60PC	W6.0mm	
911G Extended (longer head)	911G-D(extended) (flat head) (W=width; L=extended length of head)		
	911G-20D-L17	W2.0mm*L17mm (one-side tinning, no slot)	
	911G-25D-L17	W2.5mm*L17mm (one-side tinning, no slot)	
	911G-25D-L30	W2.5mm*L30mm (one-side tinning, no slot)	
	911G-26D-L30	W2.6mm*L30mm (one-side tinning, no slot)	
	911G-40D-L18	W4.0mm*L18mm (one-side tinning, no slot)	
	911G-50D-L17	W5.0mm*L17mm (one-side tinning, no slot)	
911G Extended (longer head)	911G-DV1(extended) (flat head) (W=width; L=extended length of head)		
	911G-16DV1-L17	W1.6mm*L17mm (one-side tinning, one-side slot)	
	911G-16DV1-L21	W1.6mm*L21mm (one-side tinning, one-side slot)	
	911G-20DV1-L17	W2.0mm*L17mm (one-side tinning, one-side slot)	
	911G-20DV1-L21	W2.0mm*L21mm (one-side tinning, one-side slot)	

	911G-24DV1-L17	W2.4mm*L17mm (one-side tinning, one-side slot)	
	911G-24DV1-L20	W2.4mm*L20mm (one-side tinning, one-side slot)	
	911G-25DV1-L17	W2.5mm*L17mm (one-side tinning, one-side slot)	
	911G-30DV1-L17	W3.0mm*L17mm (one-side tinning, one-side slot)	
	911G-30DV1-L25	W3.0mm*L25mm (one-side tinning, one-side slot)	
	911G-40DV1-L17	W4.0mm*L17mm (one-side tinning, one-side slot)	
	911G-40DV1-L22	W4.0mm*L22mm (one-side tinning, one-side slot)	
	911G-45DV1-L17	W4.5mm*L17mm (one-side tinning, one-side slot)	
	911G-50DV1-L19	W5.0mm*L19mm (one-side tinning, one-side slot)	